

CLAIMS

WHAT IS CLAIMED:

1. A method for providing security in a computer system, comprising:  
5 identifying information for protection;  
indicating at least one physical address of a memory that houses the information as at  
least one of read and write disabled;  
receiving a request from a program to access the information; and  
accessing the information in response to determining that the program has the  
10 authority to access the information.

2. The method of claim 1, wherein indicating at least one physical address of the  
memory includes:  
generating a table based on the physical addresses of the memory; and  
15 indicating in the table that the memory housing the information is at least one of read  
and write disabled.

3. The method of claim 2, wherein the table is a bitmap based on physical  
addresses of the memory.

4. The method of claim 1, wherein the program is an operating system.

5. The method of claim 1, wherein the information is at least one of interrupt  
descriptor table, global descriptor table, and local descriptor table.

6. The method of claim 1, wherein accessing the information in response to determining that the program has the authority to access the information includes using a stack of the computer system to verify the identity of the program.

5 7. A method for providing security, comprising:  
writing to at least one register to define a privileged memory region;  
defining at least one computer instruction as a privileged instruction, wherein the  
privileged instruction is resident in the privileged memory region;  
identifying information for protection;  
10 indicating at least one physical address of a memory that houses the information as at  
least one of read and write disabled; and  
controlling the access to the information using the privileged instruction.

15 8. The method of claim 7, further including writing to a second register, wherein  
the first and second registers define the privileged memory region.

9. The method of claim 7, wherein indicating at least one physical address of the  
memory includes:

20 generating a table based on the physical addresses of the memory; and  
indicating in the table that the memory housing the information is at least one of read  
and write disabled.

25 10. The method of claim 7, wherein the information is at least one of interrupt  
descriptor table, global descriptor table, and local descriptor table.

11. A computer readable program storage device encoded with instructions that, when executed by a computer, performs a method of providing security, comprising:

identifying information for protection;

indicating at least one physical address of a memory that houses the information as at

least one of read and write disabled;

receiving a request from a program to access the information; and

accessing the information in response to determining that the program has the authority to access the information.

12. The computer readable program storage device of claim 11, wherein indicating at least one physical address of the memory includes:

generating a table based on the physical addresses of the memory; and

indicating in the table that the memory housing the information is at least one of read and write disabled.

13. The computer readable program storage device of claim 12, wherein the table includes an entry specifying access rights to the information.

14. The computer readable program storage device of claim 11, wherein the information is at least one of interrupt descriptor table, global descriptor table, and local descriptor table.

15. An apparatus, comprising:

a memory comprising a privileged code, the privileged code capable of:

receiving a request to protect selected information;

indicating at least one physical address of a memory housing the information  
as at least one of read and write disabled;  
receiving a request from a program to access the information; and  
accessing the information in response to determining that the program has the  
authority to access the information.

16. The apparatus of claim 15, wherein the privileged code capable of indicating  
at least one physical address of the memory includes the privileged code being capable of:  
generating a table based on the physical addresses of the memory; and  
indicating in the table that the memory housing the information is at least one of read  
and write disabled.

17. The apparatus of claim 15, wherein the program is an operating system.

18. The apparatus of claim 15, wherein the information is at least one of interrupt  
descriptor table, global descriptor table, and local descriptor table.

19. A system, comprising:

a processor; and

a memory coupled to the processor, the memory comprising a privileged code capable  
of:

receiving a request to protect selected information;

indicating at least one physical address of a memory housing the information  
as at least one of read and write disabled;

receiving a request from a program to access the information; and

accessing the information in response to determining that the program has the  
authority to access the information.

20. The system of claim 19, wherein the privileged code capable of indicating at  
5 least one physical address of the memory includes the privileged code being capable of:  
generating a table based on the physical addresses of the memory; and  
indicating in the table that the memory housing the information is at least one of read  
and write disabled.

21. The system of claim 19, wherein the program is an operating system.

22. The system of claim 19, wherein the information is at least one of interrupt  
descriptor table, global descriptor table, and local descriptor table.

23. The system of claim 19, wherein the processor is an x86 processor.

24. An apparatus for providing security, comprising:  
means for identifying information for protection;  
means for indicating at least one physical address of a memory that houses the  
20 information as at least one of read and write disabled;  
means for receiving a request from a program to access the information; and  
means for accessing the information in response to determining that the program has  
the authority to access the information.